Engineering Specification

Job Name	Contractor
Job Location	Approval
	Contractor's P.O. No.
Approval	Representative

SunStat[®] CommandPlus™

Wi-Fi Programmable Touchscreen Thermostat

This all-in-one thermostat includes a built-in relay to control 120 or 240 VAC floor heating systems and a GFCI to improve safety. By default, the SunStat® CommandPlus™ controls the floor temperature. It can optionally limit the floor temperature to prevent the space from overheating, or be configured to control the space through air temperature alone.

Specifications

- P			
IOM-ST-CommandPlus Thermostat,			
ES-ST-CommandPlusThermostat			
120/240 VAC, 60 Hz, 3 watts			
15 amps resistive			
1800 watts at 120 VAC			
3600 watts at 240 VAC			
Class A (5 mA trip)			
4.73" H x 3.11" W x 1.9" D (120 x 79 x 48 mm)			
Ambient conditions 32 to 86°F (0 to 30°C), <90% RH non-condensing			
Thermistor, 10k NTC type, 300 V jacketed cable, 15' long			



Floor Sensor



Features


- Floor or air-sensing temperature control
- Remote access via Watts® Home mobile app
- Large touchscreen display
- Easy-to-use scheduling
- Portrait display
- Guided setup
- Comprehensive help screens
- Energy use monitoring
- Voltage-level sensing
- Wired connection to SunStat® R4 Relay (sold separately)
- Floor Sensor included
- 3 Year warranty



UL Listed under UL 943, UL/CSA 60730, UL 991 Listing file number E365015.

A CAUTION

This Engineering Sheet is not intended to provide full installation instructions and safety information. In order to avoid property damage or injury, please refer to the complete installation manual and product safety information provided with the product.



PRODUCT OPTIONS				
Qty	Description	Model#	Order#	
	SunStat CommandPlus Thermostat	500950-SB	81021154	
	Extra Floor Sensor (optional)	500110	81009178	
	SunStat R4 Relay (optional)	500980	81020608	

SunTouch product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact SunTouch Technical Service. Suntouch reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on SunTouch products previously or subsequently sold. Refer to the owner's manual for warranty information.



USA: T: (888) 432-8932 • F: (417) 831-4067 • SunTouch.com **Canada:** T: (888) 208-8927 • F: (905) 481-2316 **Latin America:** T: (52) 55-4122-0138 • SunTouch.com

Available at:
PEXHEAT COM